

**PRIVATE WIRE SERVICE
MILEAGE CHARGES**

Item 201 GENERAL

(M)

The regulations and charges herein apply to channels provided under this tariff, unless otherwise specified.

Mileage charges are based on the provision of standard arrangements of equipment and facilities. When it is necessary for the company to install special equipment or to incur any unusual expense in order to provide any of such channels, an additional charge may be made based on the equipment installed or other expense incurred.

When it is necessary to obtain equipment and/or facilities from another communications organization to provide a service, the Company may levy all charges imposed on it by the other organizations.

Item 202 VOICE GRADE CHANNELS

A. General

These are channels which provide voice-frequency transmission capability in the nominal frequency range of 300 to 3000 Hz and may be terminated on a two-wire or four-wire basis.

Transmission may be in one direction only or it may be in both directions, simultaneously or alternately, without additional charge.

The Company does not provide any direct current (DC) or low frequency ringing current on the channel nor does it provide DC continuity. Only alternating current, provided by the Customer and at a performance characteristics as established by the Company may be transmitted over the channel.

The channel is furnished as a Schedule 4 Type 4 (Basic) without conditioning or Company provided signalling. Additional charges will apply for conditioning as per CRTC 3003, Item 304.C to provision Type 4A, 4B and 4C.

(M₁)

Schedule IV - the numerical requirements are specified as follows:

Attenuation Distortion		Envelope Delay Distortion	
Schedule IV (in Hertz)	Overall (Note 1)	Schedule IV (in Hertz)	Overall (Note 2)
Type 4 (Basic) 500-2500 300-3000	-2 to +8 -3 to +12	Type 4 (Basic) 800-2600	1750
Type 4A (C1) 1000-2400 300-2700 300-3000	-1 to +3 -2 to +6 -3 to +12	Type 4A (C1) 1000-2400 800-2600	1000 1750
Type 4B (C2) 500-2800 300-3000	-1 to +3 -2 to +6	Type 4B (C2) 500-2600 300-3000 500-2800	500 1500 3000
Type 4C (C4) 500-3000 300-3200	-2 to +3 -2 to +6	Type 4C (C4) 1000-2600 800-2800 600-3000 500-3000	300 500 1500 3000

- Notes: 1. (-) and (+) indicate more or less loss, respectively, within the specified bandwidth.
2. Figures are microseconds between minimum and maximum delay in the specified bandwidth.

(M) - Moved from CRTC 3003, 3rd Revised Page 39

(M₁) - Moved from CRTC 3003, Original Page 39A

For explanation of symbols see Page 1

Issued: 13 June 2007

Interim Approval in Telecom Order CRTC 2007-228, 28 June 2007

Final Approval in Telecom Order CRTC 2007-294, 13 August 2007

© 2007 Northwestel Inc.

Effective: 16 July 2007